

Description

A precision wide range resistance decade box designed to meet the requirements of both industry and education. The 1040 is compact and durable, housed in a robust metal case with removable protective rubber cover, making it ideal for use in either the laboratory or field. Excellent accuracy (mid-scale 0.1 %) is achieved by using high stability metal film resistors. The 8-digit thumbwheel switch enables simple and precise setting with a clear indication of the resistance value.

Switch Contacts: Special attention has been given to the reliability of operation. A special multiple gold contact arrangement ensures low contact resistance and continued operation even if a contact fails.

Clear Visual Indication: To make selecting and reading the setting easy the 1040 incorporates colour coded digits: megohms - red, kilohms - yellow, ohms - white.

Safety Terminals: Compatible with 4 mm shrouded plugs, as well as standard plugs, bare wires, and spade terminals.

Added Protection: The 1040 comes fitted with an ergonomic rubber cover providing increased protection and durability. It has a textured grip for comfortable handling and side openings to place labels. It is easy to remove if the user prefers a stand-alone unit or to house the 1040 in the optional 9026 carry case.

Specifications

Decade	1Ω	10 Ω	100 Ω	1 kΩ	10 kΩ	100 kΩ	1 MΩ	10 MΩ
Accuracy	±1%	\pm 0.5 %	± 0.1 %	± 0.1 %	± 0.1 %	± 0.1 %	± 0.1 %	±1%
Max current	0.5 A	0.3 A	100 mA	30 mA	3 mA	0.3 mA	30 µA	3 µA
Residual resistanceLess than 250 mΩ.								
Power rating								
Voltage rating								
Temperature coefficient								
Dimensions / Weight							m / 1 kg.	

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Features

- 1 Ω to 100 MΩ
- High accuracy
- Clear visual indication
- High stability
- Low temperature coefficient
- Safety terminals
- Removable protective cover
- Suitable for industry or education

Common Applications

- Calibration of resistance in measuring devices
- PT100 simulation for checking RTD transmitters
- Select-on-test resistance substitution in circuit design
- Educational understanding of Ohm's Law

Ordering Information

1040	Wide Range Resistance Decade Box
9026	Leatherette carry case
C161	Traceable calibration certificate (Factory)
C114	Accredited calibration certificate (ISO 17025)

Time Electronics Ltd, Unit 5, TON Business Park, 2-8 Morley Road, Tonbridge, Kent, TN9 1RA, United Kingdom T: +44 (0) 1732 355993 | F: +44 (0) 1732 350198 | mail@timeelectronics.co.uk | www.timeelectronics.com